IN THE CLAIMS:

Please amend Claims 1, 3, 9, 10, 11, 13, 15, 16 and 18 as shown below and cancel Claims 5, 6, 7, 14 and 17 without prejudice or disclaimer of subject matter. The claims, as pending in the subject application, now read as follows:

 (Currently Amended) A print system comprising an external operating apparatus, a host computer which communicates with said external operating apparatus, and a printer which communicates with said host computer,

wherein said external operating apparatus comprises:

reading means for reading out image data from a detachable storage medium:

a display unit which displays a print setting screen;

an operation panel which is operative to set print settings in accordance with a print setting instruction provided by a user based on the print setting screen displayed on said display unit:

a button operative to instruct said host computer to preview the image data read out by said reading means;

transmission means for transmitting the image data read out by said reading means, to said host computer in response to said button being operated; and a controller which generates a plurality of interruption events including [[an]] a print setting information interruption event for causing said host computer to effect a preview display set therein the print settings of the image data transmitted by said

transmission means, the print setting information interruption event being generated in

accordance with said operation panel setting the print settings after the image data read out by said reading means is transmitted to said host computer by said transmission means so that the generated print setting-information interruption event includes the print settings set by said operation panel and is transmitted to said host computer,

wherein said host computer comprises:

a receiving unit which receives the image data read out by said reading means and then transmitted by said transmission means from said storage medium, and receives the plurality of interruption events generated by said controller from said external operating apparatus:

a display control unit which receives the interruption event generated by said controller from said external operating apparatus detects whether the interruption event received by said receiving unit is the print setting information interruption event, and effects the controls preview display in which such that the print settings included in the received print setting information interruption event are reflected in the image data received by said receiving unit, every time the print setting information interruption event is detected; and

a print control unit which generates print data corresponding to the print setting, wherein said printer prints the print data output from said host computer.

(Previously Presented) A system according to claim 1, wherein said controller generates the interruption event corresponding to a print start instruction. 3. (Currently Amended) A system according to claim 2, wherein[[,,]] said control unit detects whether in response to the reception of the interruption event received by said receiving unit corresponds corresponding to the print start instruction, said print control unit outputs to said printer the print data in which the print settings received by the [[a]] plurality of interruption events received so far are reflected.

4. to 8. (Canceled)

9. (Currently Amended) An information processing apparatus which can communicate with an external operating apparatus including reading means for reading out image data from a detachable storage medium, a display unit which displays a print setting screen, an operation panel which is operative to set print settings in accordance with a print setting instruction provided by a user based on the print setting screen displayed by said display unit, a preview button operative to instruct said information processing apparatus to preview the image data read out by said reading means, transmission means for transmitting the image data read out by said reading means, to said information processing apparatus in response to said preview button being operated, and a controller which generates [[an]] a plurality of interruption events including a print setting information interruption event for causing said information processing apparatus to effect a preview display set therein the print settings of the image data transmitted by said transmission means, the print setting information interruption event being generated in accordance with said operation panel setting the print settings after the image data read out by said reading means is transmitted to said information processing apparatus by said transmission means so that the generated print setting information interruption event includes the print settings

set by said operation panel and is transmitted to said information processing apparatus, and a printer, said apparatus comprising:

a receiving unit which receives the image data and the <u>plurality of</u> interruption event events transmitted from said external operating apparatus;

a display control unit which detects whether the print setting information interruption event is received by said receiving unit and effects the controls preview display in which such that the print settings included in the received print setting information interruption event are reflected in the image data received by said receiving unit, every time the print setting information event is detected; and

a print control unit which generates print data corresponding to the print setting and outputting the generated print data to said printer.

- 10. (Previously Presented) An apparatus according to claim 9, wherein said apparatus receives the interruption event corresponding to a print start instruction from said controller.
- 11. (Currently Amended) An apparatus according to claim 10, wherein <u>said</u>

 <u>control unit detects whether in response to the reception of</u> the interruption event <u>received by said</u>

 <u>receiving unit corresponds corresponding</u> to the print start instruction, said print control unit

 outputs to said printer the print data in which the print settings received by <u>the</u> [[a]] plurality of
 interruption events received so far are reflected.

12. (Canceled)

13. (Currently Amended) A method of controlling a print system comprising an external operating apparatus, a host computer which communicates with said external operating apparatus, and a printer which communicates with said host computer,

wherein said method includes a control method for said external operating apparatus, comprising the steps of:

displaying a print setting screen on a display unit;
setting, with an operation panel, print settings in accordance
with a print setting instruction provided by the user based on the print setting screen
displayed on the display unit in said displaying step;

reading out image data from a detachable storage medium:

operating a button to instruct said host computer to preview the image data read out in said reading step;

transmitting the image data read out in said reading step, to said host computer in response to said button being operated; and

generating [[an]] a plurality of interruption events including a print setting information interruption event for causing said host computer to effect a preview display set therein the print settings of the image data transmitted in said transmitting step, the print setting information interruption event being generated in accordance with the print settings being set in said setting step after the image data read out in said reading step is transmitted to said host computer in said transmitting step so that the generated print setting information interruption event is transmitted to said host computer,

wherein said method further includes a control method for said host computer, comprising the steps of:

receiving the image data read out in said reading step and then transmitted in said transmitting step, and receiving the plurality of interruption events generated in said generating step:

receiving the interruption event generated in said controlling step fromsaid external operating apparatus detecting whether the interruption event received in said
receiving step is the print setting information interruption event and effecting the
controlling preview display in which such that the print settings included in the received
print setting information interruption event is reflected in the image data received in said
image data receiving step, every time the print setting information interruption event is
detected; and

generating print data corresponding to the print setting, and

wherein said method further includes a control method for said printer by which
said printer prints printing data output from said host computer.

(Cancelled).

15. (Currently Amended) A method of controlling an information processing apparatus which can communicate with an external operating apparatus including reading means for reading out image data from a detachable storage medium, a display unit which displays a print setting screen, an operation panel which is operative to set print settings in accordance with a print setting instruction provided by a user based on the print setting screen displayed on the display unit, a preview button operative to instruct said information processing apparatus to preview the image data read out by said reading means, transmission means for transmitting the

image data read out by said reading means, to said information processing apparatus in response to said preview button being operated, and a controller for generating [[an]] a plurality of interruption events including a print setting information interruption event for causing said information processing apparatus to effect a preview display set therein the print settings of the image data transmitted by said transmission means, the print setting information interruption event being generated in accordance with said operation panel setting the print settings after the image data read out by said reading means is transmitted to said information processing apparatus by said transmission means so that the generated print setting information interruption event includes the print settings set by said operation panel and is transmitted to said information processing apparatus said method comprising:

performing by the information processing apparatus the following:

receiving the image data and the <u>plurality of interruption event events</u> transmitted from said external operating apparatus;

detecting whether the print setting information interruption event is received in said receiving step and effecting controlling the preview display in which such that the print settings included in the received print setting information interruption event are reflected in the image data received in said receiving step, every time the print setting information is detected; and

generating print data corresponding to the print setting and outputting the generated print data to said printer.

16. (Currently Amended) A program stored on a computer-readable recording medium, for causing a computer to execute a method of controlling a print system comprising an external operating apparatus, a host computer which communicates with said external operating apparatus, and a printer which communicates with said host computer,

wherein said method includes a control method for said external operating apparatus and comprises the steps of:

reading out image data from a detachable storage medium;

displaying a print setting screen on a display unit;

setting, with an operation panel, print settings in accordance with a print setting instruction provided by a user based on the print setting screen displayed on the display unit;

operating a button to instruct said host computer to preview the image data read out in said reading step;

transmitting the image data read out in said reading step, to said host computer in response to said button being operated; and

generating [[an]] a plurality of interruption events including a print setting information interruption event for causing said host computer to effect a preview display set therein the print settings of the image data transmitted in said transmitting step, the print setting information interruption event being generated in accordance with the print settings being set in said setting step after the image data read out in said reading step is transmitted to said host computer in said transmitting step so that the generated print setting information interruption event includes the print settings set in said setting step and is transmitted to said host computer,

wherein said method further includes a control method for said host computer and comprises the steps of:

receiving the image data read out in said reading step and then transmitted in said transmitting step, and receiving the plurality of interruption events generated in said generating step:

receiving the interruption event generated in said controlling step fromsaid external operating apparatus detecting whether the interruption event received in said
receiving step is the print setting information interruption event, and effecting the
controls preview display-in-which such that the print settings included in the received
print setting information interruption event [[is]] are reflected in the image data received
in said image data receiving step, every time the print setting information interruption
event is detected; and

generating print data corresponding to the print setting, and

wherein said method further includes a control method for said printer by which
said printer prints the print data output from said host computer.

(Cancelled).

18. (Currently Amended) A program stored on a computer-readable medium, for causing a computer to execute a method of controlling an information processing apparatus which can communicate with an external operating apparatus including reading means for reading out image data from a detachable storage medium, a display unit which displays a print setting screen, an operation panel which is operative to set print settings in accordance with a print setting instruction provided by a user based on the print setting screen displayed on the display unit, a preview button operative to instruct said information processing apparatus to

preview the image data read out by said reading means, transmission means for transmitting the image data read out by said reading means, to said information processing apparatus in response to said preview button being operated, and a controller for generating [[an]]a plurality of interruption events including a print setting information interruption event for causing said information processing apparatus to effect a preview display set therein the print settings of the image data transmitted by said transmission means, the print setting information interruption event being generated in accordance with said operation panel setting the print settings after the image data read out by said reading means is transmitted to said information processing apparatus by said transmission means so that the generated print setting information interruption event includes the print settings set by said operation panel and is transmitted to said information processing apparatus, and a printer, said method comprising the steps of:

receiving the image data and the <u>plurality of interruption event events</u> transmitted from said external operating apparatus;

detecting whether the print setting information interruption event is received in said receiving step and effecting controlling the preview display in which such that the print settings included in the received print setting information interruption event [[is]] are reflected in the image data received in said receiving step, every time the print setting information interruption event is detected; and

generating print data corresponding to the print setting and outputting the generated print data to said printer.